



SPECIFICATION INFORMATION SHEET

ENGINE	Zetec 16 valve DOHC Fuel Inj	
	Bore	84.8mm
	Stroke	88 mm
	Compression rate	10:1
	Valves	16
	Camshafts	2 in cylinder head
	Firing order	1:3:4:2
	Power	112kw@6000rpm
	Torque	140ft/lbs@5000rpm
	Capacity	2000cc
PERFORMANCE	0 – 100 KM/H	5.2 sec
	Maximum speed	200km/h (approx)
TRANSMISSION	5 Speed Manual	
	Ratio's	1 st 3.36:1
		2 nd 1.81:1
		3 rd 1.26:1
		4 th 1.00:1
		5 th 0.82:1
		Reverse 3.87:1
	Final drive ratios	Options 3.89:1
		4.11:1
	LSD Option Available	
CLUTCH		216mm Single dry plate *Hydraulic
BRAKES		Dual Circuit hydraulic Alloy pedal box, position adjustable. Adjustable brake bias Fluid level warning system
	Front	257 mm diameter ventilated discs With 4 pot alloy calipers
	Rear	229 mm diameter solid discs with Single pot alloy calipers and handbrake mechanism.
SUSPENSION	Front & Rear	Independent Elliptical double wishbones Adjustable anti-roll bars.
	Dampers	Coil spring over adjustable hydraulic Dampers.

WHEELS & TYRES

15"/7" alloy wheels
195 /50 * 15 tyres
Spare Optional

FUEL TANK:**Capacity**

40litres

INSTRUMENTATION**VDO**

Speedometer, Tachometer, Ammeter,
Oil pressure, Temperature & Fuel
gauge.

INTERIOR

Bucket seats, (Driver seat
Adjustable)
Upholstery. Black vinyl.

STANDARD EQUIPMENT

Roll bar,
Cycle type front fenders
Heated windscreen
Side mounted rear view mirrors.

COLOUR**Alloy Body Panels
Mudguards
Nose Cone
Cycle Fenders**

Natural aluminium finish
Painted one standard colour
Painted one standard colour
Painted one standard colour

Standard Colours

Green / Red / Blue / Yellow /
White / Black.

GENERAL DIMENSIONS

Length	3500 mm
Width	1575 mm
Height	1060 mm (to roll bar)
Front track	1410 mm
Rear track	1410 mm
Wheel base	2225 mm
Ground clearance	110 mm

輸入販売元： 株式会社 鈴商

〒465-0065 愛知県名古屋市名東区梅森坂 3-823

tel052-703-1131 fax052-703-1157

e-mail info@suzusho.com <http://www.suzusho.com>